

PRESS SPECIFICATIONS

Size	22'3.5" x 5'4.5" x 6'9" (W x D x H) / 6.79 m x 1.63 m x 2.06 m (W x D x H)
Weight	6,769 lb (3,070 kg) base configuration

COLOR ACCELERATOR SPECIFICATIONS

Size	6.59' (Length) / 2.01 m (Length)
Weight	1,650 lb (748.4 kg)

PRINT SERVER SPECIFICATIONS

Digital Front End	Xerox® FreeFlow® Print Server
Data Streams	PDF, PDF-VT, IPDS, PostScript, TIFF, JPEG, PPML, VIPP, LCDS

PRINT ENGINE TECHNOLOGY

Print Resolution	True High Definition 1200 x 1200 dpi
Drop Volumes	4.5 pL multi-bit simulation option (small, medium, large, max)
Automated Intelligence	Intelli-Purge, True Dot, Clear Pixel Plus, Auto IoP, Auto Registration, Anti-aliasing
K-Only Mode	Unique option to cap cyan, magenta and yellow heads when printing in black and white
Maximum Image Area	13.76" x 20.25" / (350 mm x 514 mm)

PRODUCTIVITY

Images Per Minute	A4 / 8.5" x 11" / 8.5" x 14" (LEF) – 197 simplex / 270 duplex ipm A3 / 11" x 17" – 200 simplex / 300 duplex ipm (2-up) Up to 18,000 images per hour
-------------------	---

PAPER

Paper Characteristics	Uncoated plain, inkjet treated, offset coated (gloss, silk, satin, matte, dull) paper, tabbed and drilled stock
Paper Weight	60 – 300 gsm (16# bond to 110# cover) See the Baltoro Tested Substrate List for the latest supported media

FEEDING / PAPER SUPPLY

Capacity	10" (254 mm) of stock per tray / 2,500 sheets (.004 caliper, 90 gsm)
Feeder Module	Two trays/drawers per Feeder Module Maximum of four (4) Feeder Modules/eight (8) paper drawers – total of 20,000 sheet capacity
Optional High Capacity Feeder	
Minimum Sheet Size	7.0" x 10.0" / (177.8 mm x 254 mm)
Maximum Sheet Size	14.33" x 20.5" / (364 mm x 520 mm)
Load While Run	All paper drawers
Optional	Tecnaue SheetFeeder BV

FINISHING*

Stacking	Xerox® Production Stacker – 5,700 sheets stacking capacity – Unload while run without interruption – Stacks 6.9" x 9.8" LEF to 14.3" x 19.7" (175 mm x 249 mm to 364 mm x 500 mm) sheets Optional Second Xerox® Production Stacker Multigraf PST-52 Stacker CP Bourg BDFNx / BDFE-x Booklet Maker – 22 sheet capacity with optional corner edge stapling CP Bourg BME – 30 sheet capacity with optional corner edge stapling Watkiss PowerSquare 224 – Sticking, folding and trimming with optional cover feeder – 52 sheets, 6 position staple
Booklet Making	CP Bourg BB3202 Inline Perfect Binder – Binds from 1 to 60 mm (0.04" to 2.36") with support for EVA or PUR Xerox® Tape Binder – Binds up to 100 sheets Tecnaue TC 1530 Dynamic Perforator – Static, still and dynamic perforations with optional 2D bar code reader – Up to 2 horizontal perf cylinders and 4 vertical perf wheels GBC Fusion Punch II CP Bourg BSF – Dual mode sheet feeding
Binding	
Dynamic Perforation	
Punching	
Sheet Feeding	

AVERAGE PRINT VOLUME

Recommended	750,000 – 3,000,000 per month
Duty Cycle	6,000,000

* See your Xerox representative for availability